



imagination at work

GE Water & Process Technologies

Tonkaflo Pump Model AS4014G

[CUTSHEET](#) |
 [CURVE](#) |
 [DRAWING](#) |
 [CAD SYMBOLS](#) |
 [OPTIONS](#) |
 [SUMMARY](#)

Operation at 40.0 gpm

Pressure Boost **114.9 psi**
 Efficiency **58%**
 NPSH **8 feet**
 Brake **5 HP**

Flow Range

Minimum **20.0 gpm**
 Maximum **55.0 gpm**

Connections

Inlet **2 inch Victaulic**
 Discharge **1-1/2 inch Victaulic**

Stages

Stages **14**

Motor

HP **N/A**
 RPM **N/A**
 Enclosure **N/A**
 Voltage **N/A**
 Frequency **N/A**
 Phase **N/A**

Bedplate

N/A

Seals

Arrangement **Standard**
 Max Inlet Pres **200 psi**
 Max Dis Pres **750 psi**

Material

Inlet Housing **304SS**
 Discharge Housing **316SS**
 Shell **304SS**
 Shaft **304SS**
 Stages **304SS**
 Mech Seal Elast **Buna-N**
 Shell/Seal O-rings **Buna-N**
 Int Stage Seals **Buna-N**
 Shaft Bearings **Buna-N**

Shipping

Weight **78 lbs.**
 Dimensions **49 x 13 x 12 in.**
(L x W x H)

Description	Part Number	List Price (USD)
AS4014G-Pump Only	1122939	\$3,992.00
		TOTAL: \$3,992.00

Prices are suggested retail price and are subject to change without notice.

*Viton and Teflon are trademarks of E.I. DuPont de Nemours and Company, Inc.

Copyright General Electric Company 1997-2010