



imagination at work

GE Water & Process Technologies

## Tonkaflo Pump Model AS2523G

[CUTSHEET](#) | 
 [CURVE](#) | 
 [DRAWING](#) | 
 [CAD SYMBOLS](#) | 
 [OPTIONS](#) | 
 [SUMMARY](#)

### Operation at 5.0 m3/hr

Pressure Boost **16.3 bar**  
 Efficiency **60%**  
 NPSH **4 meters**  
 Brake **4 kW**

### Flow Range

Minimum **2.27 m3/hr**  
 Maximum **7.27 m3/hr**

### Connections

Inlet **1-1/4 inch Victaulic**  
 Discharge **1-1/4 inch Victaulic**

### Stages

Stages **23**

### Motor

HP **5.0**  
 RPM **3450**  
 Enclosure **TEFC**  
 Voltage **230/460 VAC**  
 Frequency **60**  
 Phase **3**

### Bedplate

N/A

### Seals

Arrangement **Standard**  
 Max Inlet Pres **14 bar**  
 Max Dis Pres **52 bar**

### Material

Inlet Housing **316SS**  
 Discharge Housing **316SS**  
 Shell **304SS**  
 Shaft **304SS**  
 Stages **304SS**  
 Mech Seal Elast **Buna-N**  
 Shell/Seal O-rings **Buna-N**  
 Int Stage Seals **Buna-N**  
 Shaft Bearings **Buna-N**

### Shipping

Weight **88 kgs.**  
 Dimensions **155 x 41 x 38 cm.**  
*(L x W x H)*

Description	Part Number	List Price (USD)
AS2523G-Pump Close-Coupled to 5 HP Motor, 3Ø, TEFC, 184TC, 1.15SF	1123773	\$3,548.00
		<b>TOTAL: \$3,548.00</b>

Prices are suggested retail price and are subject to change without notice.

\*Viton and Teflon are trademarks of E.I. DuPont de Nemours and Company, Inc.

Copyright General Electric Company 1997-2010