



GE Water & Process Technologies

Tonkaflo Pump Model SS5524KZC

[CUTSHEET](#)
[CURVE](#)
[DRAWING](#)
[CAD SYMBOLS](#)
[OPTIONS](#)
[SUMMARY](#)

Operation at 55.0 gpm

Pressure Boost **504.2 psi**
 Efficiency **60%**
 NPSH **16 feet**
 Brake **27 HP**

Motor

HP **30.0**
 RPM **3450**
 Enclosure **TEFC**
 Voltage **230/460 VAC**
 Frequency **60**
 Phase **3**

Material

Inlet Housing **316SS**
 Discharge Housing **316SS**
 Shell **316SS**
 Shaft **316SS**
 Stages **Noryl**
 Mech Seal Elast **Buna-N**
 Shell/Seal O-rings **Buna-N**
 Int Stage Seals **N/A**
 Shaft Bearings **Buna-N**

Flow Range

Minimum **20.0 gpm**
 Maximum **74.0 gpm**

Bedplate

N/A

Connections

Inlet **3 inch Victaulic**
 Discharge **3 inch Victaulic**

Seals

Arrangement **Standard**
 Max Inlet Pres **200 psi**
 Max Dis Pres **750 psi**

Shipping

Weight **886 lbs.**
 Dimensions **115 x 31 x 31 in.**
 (L x W x H)

Stages

Stages **24**

Description	Part Number	List Price (USD)
SS5524KZC-Pump Close-Coupled to 30 HP Motor, 3Ø, TEFC, 286TSC, 1.15SF	1123976	\$8,328.00
		TOTAL: \$8,328.00

Prices are suggested retail price and are subject to change without notice.

*Viton and Teflon are trademarks of E.I. DuPont de Nemours and Company, Inc.

Copyright General Electric Company 1997-2010