



imagination at work

GE Water & Process Technologies

Tonkaflo Pump Model SS12519KZE

[CUTSHEET](#) |
 [CURVE](#) |
 [DRAWING](#) |
 [CAD SYMBOLS](#) |
 [OPTIONS](#) |
 [SUMMARY](#)

Operation at 125.0 gpm

Pressure Boost **486.4 psi**
 Efficiency **61%**
 NPSH **11 feet**
 Brake **58 HP**

Flow Range

Minimum **40.0 gpm**
 Maximum **190.0 gpm**

Connections

Inlet **3 inch Victaulic**
 Discharge **3 inch Victaulic**

Stages

Stages **19**

Motor

HP **60.0**
 RPM **3450**
 Enclosure **TEFC**
 Voltage **230/460 VAC**
 Frequency **60**
 Phase **3**

Bedplate

N/A

Seals

Arrangement **Standard**
 Max Inlet Pres **200 psi**
 Max Dis Pres **750 psi**

Material

Inlet Housing **316SS**
 Discharge Housing **316SS**
 Shell **316SS**
 Shaft **316SS**
 Stages **Noryl**
 Mech Seal Elast **Buna-N**
 Shell/Seal O-rings **Buna-N**
 Int Stage Seals **N/A**
 Shaft Bearings **Buna-N**

Shipping

Weight **1381 lbs.**
 Dimensions **134 x 39 x 35 in.**
(L x W x H)

Description	Part Number	List Price (USD)
SS12519KZE-Pump Close-Coupled to 60 HP Motor, 3Ø, TEFC, 364TSC, 1.15SF	1123986	\$13,574.00
		TOTAL: \$13,574.00

Prices are suggested retail price and are subject to change without notice.

*Viton and Teflon are trademarks of E.I. DuPont de Nemours and Company, Inc.

Copyright General Electric Company 1997-2010